

CINEMA SUBWOOFER C18SW



Cinema Screen Subwoofer System

Designed to provide the visceral bedrock for PLF and commercial screens up to 75 feet, the C18SW brings explosive low-frequency extension to our Pro Cinema range. At its core is a world-class 18-inch Lavoce driver from Italy, housed within a precision-engineered tri-ported enclosure to deliver deep, high-impact Low-Frequency Effects (LFE) with effortless authority. Perfectly matched for Dolby Atmos, Dolby 7.1, and DTS:X setups, this high-performance subwoofer ensures that every rumble, impact, and subtle sub-bass nuance is felt exactly as the filmmakers intended.


APPLICATIONS

Screen Channel LFE
Surround Channel LFE
Private Theatres
VIP Home Cinema

3 YEARS*
Warranty



FEATURES



SPECIFICATIONS

MODEL	C18SW
Configuration	Cinema Screen / Surround Channel Subwoofer System
Frequency Range	30 Hz to 1400 Hz
Power LF (AES)	700 Watts
Sensitivity LF	100 dB
Nominal Impedance	8 Ohms
Maximum SPL	128 dB
Recommended Amp Power	1000 Watts (RMS) at 8 Ohms
Recommended Amplifier	DB Sound DB1500
Low Frequency Driver	Single 18 Inch (380mm) paper cone driver with 4 Inch (100mm) Voice Coil
Connectors	4 Pin Barrier Terminal Block Connector
Enclosure Material	18mm Birch Plywood
Finish	Textured Black Paint
Dimensions	1210 mm x 575 mm x 400 mm
Weight	46.30 Kgs

