



Pro Cinema. Sounds Great!

SURROUND CHANNEL S1020



Cinema Surround Speaker System

This high-performance 2-way passive surround loudspeaker, the S1020, brings enhanced power and precision to larger auditoriums and is engineered to handle expansive cinema halls up to 50 feet wide. It features a robust, braced cabinet designed to achieve superior sound distribution while effectively mitigating undesirable ceiling reflections. At its core, a world-class 10-inch Lavoce low-frequency driver pairs with a 1-inch exit compression driver on an 80° x 60° constant directivity horn for exceptionally precise control. This system delivers unmatched acoustic depth and efficiency, making it the definitive choice for high-demand Dolby Atmos, Dolby 7.1, and DTS:X environments.




APPLICATIONS

Cinemas	Multiplexes	Megaplexes
PLF Screens	Surround Channels	Overhead Channels



FEATURES



* Terms & Condition Apply

SPECIFICATIONS

MODEL	S1020
Configuration	Two-Way Cinema Surround System
Frequency Range	60 Hz to 18 KHz
Power (AES)	250 Watts
Sensitivity	107 dB
Nominal Impedance	8 Ohms
Maximum SPL	130 dB
Coverage Pattern	80° H x 60° V
Recommended Amp Power	250 Watts (RMS) at 8 Ohms
Recommended Amplifier	DB Sound DB600
Driver	Single 10 Inch LF Driver with 1 Inch HF Mounted in a constant Directivity Horn
Crossover Frequency	2500 Hz
Connectors	4 Pin Barrier Terminal Block Connector
Mounting	Fixed U Brackets / 4 Point Tilt & Swivel Bracket
Enclosure Material	18mm Birch Plywood
Grille	Black Cloth
Finish	Textured Black Paint
Dimensions	485 mm x 400 mm x 270 mm
Weight	12.00 Kgs

