

DB Sound BP Series Power Amplifiers are 4 Channel Amplifiers which comes in compact 2U Designs makes the amplifies occupy less space with high power.



### APPLICATIONS

- A/V Portable
- Music Reproduction
- Pro Audio Installs
- Commercial Cinema Applications
- Installed Sound reinforcement

### FEATURES

- Compact 2U Design
- Versatile Sound reinforcement
- Rugged Construction
- Defended Gain Controls
- Neutrik Speakon Outputs
- Class H Hybrid

### SPECIFICATIONS

MODEL	BP-404
Output 8Ohms 1KHz0.1% THD stereo Mode	4 x 450W
Output 4Ohms 1KHz0.1% THD stereo Mode	4 x 600W
Output 8Ohms 1KHz0.1% THD bridge Mode	2 x 1200W
Output 4Ohms 1KHz0.1% THD bridge Mode	2 x 1800W
Signal / noise	106dB
Slew Rate	83v/us
Damping factor	560:1
Fuse	T25A
Power Supply	220V 50/60Hz
Input Sensitivity	0.775V,1.0V,1.4V
Frequency Response @1 Watt into 8 Ohm	±0.1dB, 20Hz -20kHz
THD+N	≤0.01% @ 8Ω1kHz
IMD	≤0.01% @ 8Ω at rate output
Input Impedance	30k Ohm Balanced or 15k Ohm Unbalanced
Crosstalk at Rated Output 8 Ohms 1kHz	≤-70dB
Input CMRR	≤-75dB
Indicators	Signal, Protect, Clip, Limited
Net Weight	27kgs
Dimensions(mm)	483W x 492D x 90H